

Listing of Claims:

1. (Canceled)
2. (Canceled)
3. (Currently Amended) ~~The A lid support of claim 1, wherein said comprising:~~
a support platform is tapered to provide a narrower portion and wider portion[[,]]; ~~and said plurality of platform support legs includes a serrated support leg and two opposed support legs, said~~
a serrated support leg extending downwardly and outwardly proximate a front edge of said narrower portion[[,]]; and ~~said~~
two opposed support legs extending downwardly proximate a rear edge of said wider portion, wherein the combined structure of said support platform, said serrated support leg and said opposed support legs is such that a plurality of the lid supports are able to be intimately stacked for efficient storage.
4. (Currently amended) A lid support comprising:
a support platform;
at least one leg supporting said support platform above a support surface; and
a serrated edge extending downwardly and outwardly from said support platform toward said support surface.
5. (Original) The lid support of claim 4, wherein said support platform includes a grasping member such that the support platform serves as a handle to use said serrated edge as a cutting implement.
6. (Original) The lid support of claim 5, wherein said grasping member is a hole in said support platform.

7. (Original) The lid support of claim 4, wherein said serrated edge is provided on a serrated support leg.
8. (Currently amended) The lid support of claim 7, ~~further comprising:~~ wherein said at least one leg supporting said support platform includes said serrated leg and at least two platform support legs extending downwardly from said support platform, such that said serrated support leg and said at least two platform support legs maintain said support platform in a substantially horizontal plane.
9. (Original) The lid support of claim 8, wherein the combined structure of said support platform, said serrated support leg, and said platform support legs is such that a plurality of the lid supports are able to be intimately stacked for efficient storage.
10. (Original) The lid support member of claim 9, wherein said support platform is tapered to provide a narrower portion and wider portion, said serrated support leg extending downwardly and outwardly from a front edge of said narrower portion, and said platform support legs extending downwardly from a rear edge of said wider portion.